




# F F SERIES



## Recommended applications

Residential	Bath / Shower	Wall
Light commercial	Fireplace	Floor
Medium commercial	Indoor	Outdoor

## Characteristics of tile

Low maintenance	Fade resistant	Resistant to fungus
Stain resistant	Hypoallergenic	Odour resistant

## Technical specifications

Pattern Repeat	Faces: 13 - 24x48 25-24x24, 50-12x24	MOHS	6
PEI	4 Dark/Brown 5 Grey	Tile thickness	10 mm 24x48, 24x24 9.5mm 12x24
Frost Resistance	Yes	Chemical Resistance	GA Grade
Water Absorption	0.1%	Variation	V1  V2  V3  V4 Substantial

## Sizes and Finishes

	12x24	24x24	24x48
Ardesie Dark	✓	✓	✓
Ardesie Grey	✓	✓	✓
Ardesie Multicolor	✓	✓	✓
Ardesie White	✓	✓	✓

## Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

Burnaby: 4330 Halifax Street T: 604-298-6252  
 Nanaimo: 4337 Boban Drive T: 250-729-9766  
 Port Coquitlam: 1110-1579 Kingsway Ave T: 778-948-9854