VINUS SERIES

GLAZED PORCELAIN





Vinus Charcoal





Vinus Grey



Vinus Moka



Vinus Warm Black









Recommended applications

Residential	Bath / Shower	₩ Wall
Light commercial	Fireplace	Floor
Medium commercial	film Indoor	

Sizes and Finishes

12x24

Natural / Rectified

Characteristics of tile

X	Low maintenance	* Fade resistant	Resistant to fungus
ď,	Stain resistant	* Hypoallergenic	

Technical specifications

	Pattern Repeat	n/a	*	MOHS		n/a	
99	PEI	4	P	Tile thickness		10 mm	
**	Frost Resistance	Yes	İ	Chemical Resistance	n/a		
٥.	Water Absorption	n/a		Variation	V1 V1	V2 V3	V4
4					Uniform		

Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample.

Technical data is supplied by the manifacturer and is subject to change at anytime.

For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

Burnaby: 4330 Halifax Street T: 604-298-6252 Port Coquitlam: 1110-1579 Kingsway Ave T: 778-948-9854 Nanaimo: 4337 Boban Drive T: 250-729-9766 Courtenay: 2-2989 Kilpatrick Ave T: 250-871-3122



citytile.ca