

H F SERIES

GLAZED PORCELAIN



Arkety ris

Arkety Perla

Recommended applications

| | | |
|-------------------|---------------|-------|
| Residential | Bath / Shower | Wall |
| Light commercial | Fireplace | Floor |
| Medium commercial | Indoor | |

Characteristics of tile

| | | |
|-----------------|----------------|---------------------|
| Low maintenance | Fade resistant | Resistant to fungus |
| Stain resistant | Hypoallergenic | Odour resistant |

Technical specifications

| | | | |
|----------------------|-----|---------------------|--|
| Pattern Repeat | n/a | MOHS | n/a |
| PEI | n/a | Tile thickness | 8.5 mm |
| Frost Resistance | Yes | Chemical Resistance | n/a |
| Friction Coefficient | n/a | Variation | V1 V2 V3 V4 Slight |
| Slip Resistance | n/a | | |
| Water Absorption | n/a | | |

Sizes and Finishes



| | |
|-----------------------|--|
| Trevi Blanco Polished | |
| Fontana Blanco Matte | |

Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

Burnaby: 4330 Halifax Street T: 604-298-6252
 Port Coquitlam: 1110-1579 Kingsway Ave T: 778-948-9854
 Nanaimo: 4337 Boban Drive T: 250-729-9766
 Courtenay: 2-2989 Kilpatrick Ave T: 250-871-3122

