

ARKETY SERIES

GLAZED PORCELAIN



Arkety Gris



Arkety Perla



Recommended applications

Residential	Bath / Shower	Wall
Light commercial	Fireplace	Floor
Medium commercial	Indoor	

Characteristics of tile

Low maintenance	Fade resistant	Resistant to fungus
Stain resistant	Hypoallergenic	Odour resistant

Technical specifications

Pattern Repeat	n/a	MOHS	n/a
PEI	n/a	Tile thickness	8.5 mm
Frost Resistance	Yes	Chemical Resistance	n/a
Friction Coefficient	n/a	Variation	V1 V2 V3 V4
Slip Resistance	n/a		Slight
Water Absorption	n/a		

Sizes and Finishes

	24x24
Arkety Gris Matte	✓
Arkety Perla Matte	✓

Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

Burnaby: 4330 Halifax Street T: 604-298-6252
Port Coquitlam: 1110-1579 Kingsway Ave T: 778-948-9854
Nanaimo: 4337 Boban Drive T: 250-729-9766
Courtenay: 2-2989 Kilpatrick Ave T: 250-871-3122
citytile.ca

