

BRICOLA SERIES

GLAZED PORCELAIN



Bricola Bianco



Bricola Greige



Bricola Miele











Bricola Noce



Bricola Ebano



Recommended applications


| | |
|--|---|
|  Floor |  Wall |
|  Residential |  Bath / Shower |
|  Light commercial |  Fireplace |
|  Medium commercial |  Indoor |




Bianco



Greige



Miele



Noce









Ebano
















Sizes and Finishes

| | 8x48 | Spina 20x12 | Step 12x48 |
|----------------------|------|-------------|------------|
| Bricola Bianco Rect. | ✓ | ✓ | ✓ |
| Bricola Greige Rect. | ✓ | ✓ | ✓ |
| Bricola Miele Rect. | ✓ | ✓ | ✓ |
| Bricola Noce Rect. | ✓ | ✓ | ✓ |
| Bricola Ebano Rect. | ✓ | ✓ | ✓ |

Characteristics of tile

| | | |
|--|--|---|
|  Low maintenance |  Fade resistant |  Resistant to fungus |
|  Stain resistant |  Hypoallergenic |  Odour resistant |

Technical specifications

| | | | |
|--|------------------------|---|---|
|  Pattern Repeat | n/a |  MOHS | 6 |
|  PEI | 4 |  Tile thickness | 10mm |
|  Frost Resistance | Yes |  Chemical Resistance | GHA |
|  Water Absorption | 0.2% |  Variation |  V1  V2  V3  V4 Moderate |
|  Dynamic Coefficient of Friction | n/a | | |
|  Friction Coefficient | > 0.74Wet > 0.84Dry | | |
|  Slip Resistance | A | | |

Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.