

SARDONYX SERIES

PORCELAIN TILE



Recommended applications

Residential	Bath / Shower	Wall
Light commercial	Fireplace	Floor
Medium commercial	Indoor	

Characteristics of tile


Low maintenance	Fade resistant	Resistant to fungus
Stain resistant	Hypoallergenic	Odour resistant

Technical specifications

Pattern Repeat	n/a	MOHS	n/a
Slip Resistance	n/a	Tile thickness	9 mm
Frost Resistance	Yes	Chemical Resistance	A Resistance
Water Absorption	n/a	Variation	V1 V2 V3 V4 High



Sardonyx Pearl



Sardonyx Cream



Sardonyx White

Sizes and Finishes

	24x48	36x36	36x70
Sardonyx Pearl Polished	✓	✓	✓
Sardonyx Cream Polished	✓	✓	✓
Sardonyx White Polished	✓	✓	✓

Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

Burnaby: 4330 Halifax Street T: 604-298-6252
 Port Coquitlam: 1110-1579 Kingsway Ave T: 778-948-9854
 Nanaimo: 4337 Boban Drive T: 250-729-9766
 Courtenay: 2-2989 Kilpatrick Ave T: 250-871-3122

