

# TIMELESS SERIES

## PORCELAIN



Timeless Ecu



Timeless Greige



Timeless Honey











Timeless Ivory









Timeless Nut


















## Recommended applications

 Floor	 Wall
 Residential	 Bath / Shower
 Light commercial	 Fireplace
 Medium commercial	 Indoor

## Characteristics of tile

 Low maintenance	 Fade resistant	 Resistant to fungus
 Stain resistant	 Hypoallergenic	 Odour resistant

## Technical specifications

 Pattern Repeat	24	 MOHS	7
 PEI	n/a	 Tile thickness	8.5mm
 Frost Resistance	Yes	 Chemical Resistance	A, HA
 Water Absorption	≤ 0.5%	 Variation	 V1  V2  V3  V4 Moderate
 Dynamic Coefficient of Friction	n/a		
 Friction Coefficient	n/a		
 Slip Resistance	R10		



Ecu Chevron



Greige Chevron



Honey Chevron



Ivory Chevron



Nut Chevron

## Sizes and Finishes

	9.5x60	24x48 Chevron
Timeless Ecu	✓	✓
Timeless Greige	✓	✓
Timeless Honey	✓	✓
Timeless Ivory	✓	✓
Timeless Nut	✓	✓

## Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.