

# EVOQUE / BIANCO LASA SERIES

RECTIFIED PORCELAIN



## Recommended applications

Residential	Bath / Shower	Wall
Light commercial	Fireplace	Floor
Medium commercial	Indoor	

## Characteristics of tile

Low maintenance	Fade resistant	Resistant to fungus
Stain resistant	Hypoallergenic	Odour resistant

## Technical specifications

Pattern Repeat	12x24-110, 24x24- 55, 24x48 and 48x48- 30	MOHS	n/a
PEI	3-5	Tile thickness	10mm
Frost Resistance	Yes	Chemical Resistance	Class B
Dynamic Coefficient of Friction	n/a	Variation	V1  V2  V3  V4
Friction Coefficient	n/a		
Slip Resistance	R10		
Water Absorption	≤ 0.5%		

## Sizes and Finishes

	12x24	24x24	24x48	48x48
Polished	✓	✓	✓	✓
Matte	✓	✓	✓	n/a

## Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

Burnaby: 4330 Halifax Street T: 604-298-6252  
 Port Coquitlam: 1110-1579 Kingsway Ave T: 778-948-9854  
 Nanaimo: 4337 Boban Drive T: 250-729-9766  
 Courtenay: 2-2989 Kilpatrick Ave T: 250-871-3122

