LIVA SERIES

GLAZED PORCELAIN









Recommended applications









Liva Dark Grey

Liva Light Grey

Liva White





Liva Beige

Liva Black

Characteristics of tile

X	Low maintenance	**	Fade resistant		Resistant to fungus
ď.	Stain resistant	×	Hypoallergenic	m X	Odour resistant
Ter	hnical specification	ns			

iecnnicai specifications

	Pattern Repeat	n/a	₩	MOHS		n/a	
••	PEI	4	P	Tile thickness		10 mm	
**	Frost Resistance	Yes	İ	Chemical Resistance		min UB	
٥.	Water Absorption	< 0.5%	▦	Variation	V1		V4
					Cliabt		

Sizes and Finishes

	12x24	24x24	24x48	2x2
Liva Dark Grey Polished				
Liva Dark Grey Matte				
Liva Light Grey Polished				
Liva Light Grey Matte				
Liva White Polished				
Liva White Matte				
Liva Beige Polished			Ť	
Liva Beige Matte				
Liva Black Matte	/			

Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

> Burnaby: 4330 Halifax Street T: 604-298-6252 Port Coquitlam: 1110-1579 Kingsway Ave T: 778-948-9854 Nanaimo: 4337 Boban Drive T: 250-729-9766 Courtenay: 2-2989 Kilpatrick Ave T: 250-871-3122

