

GANI MARBLE SERIES

36 X 70 GLAZED PORCELAIN SLABS



Statuario Calacatta Pol. 2809BH



White Onyx Pol. 2806BH



Olympia White Pol. 2906BM



Calacatta Mint Satin Pol. 2911SP

Recommended applications

Residential	Bath / Shower	Wall
Light commercial	Fireplace	Floor
Medium commercial	Indoor	

Characteristics of tile

Low maintenance	Fade resistant	Resistant to fungus
Stain resistant	Hypoallergenic	Odour resistant

Technical specifications

Pattern Repeat		MOHS	n/a
PEI	4	Tile thickness	10.5 mm
Dynamic Coefficient of Friction	Matte: 0.5	Chemical Resistance	GA Grade
Friction Coefficient	Wet: 0.62 Dry: 0.83	Variation	V1 V2 V3 V4 Substantial
Frost Resistance	Yes		
Water Absorption	0.5 %		

Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample.
For rectangular tiles, for both floor and wall, are not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

NOTE: Stair nosing and mosaics available by special order.

Burnaby: 4330 Halifax Street T: 604-298-6252
Port Coquitlam: 1110-1579 Kingsway Ave T: 778-948-9854
Nanaimo: 4337 Boban Drive T: 250-729-9766
Courtenay: 2-2989 Kilpatrick Ave T: 250-871-3122

