# WHITE 3D SERIES

### **CERAMIC TILE**





Bath / Shower

Fireplace

indoor

Wall





Acoustic White



White 3D Glossy

White Snowflake Glossy

White Diamond Glossy

Rainfall White

#### Characteristics of tile

Residential

Light commercial

Medium commercial

**Recommended applications** 

X	Low maintenance	*	Fade resistant	• •	Resistant to fungus
ď,	Stain resistant	×	Hypoallergenic	m <b>A</b>	Odour resistant
Ted	chnical specification	ns			

## **Sizes and Finishes**

12x24	
<b>√</b>	
$\overline{}$	
<b>/</b>	
	12x24

	Pattern Repeat	n/a	<b>**</b>	MOHS		n/	n/a	
*•	PEI	n/a	P	Tile thickness		9 r	nm	
**	Frost Resistance	n/a	İ	Chemical Resistance				
۵۰	Water Absorption	n/a		Variation		V2	V3	V4
					Uniform			

### **Special instructions**

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

