

ATLANTIS SERIES

RECTIFIED PORCELAIN



Recommended applications

Residential	Bath / Shower	Wall
Light commercial	Fireplace	Floor
Medium commercial	Indoor	

Characteristics of tile

Low maintenance	Fade resistant	Resistant to fungus
Stain resistant	Hypoallergenic	Odour resistant

Technical specifications

Pattern Repeat	n/a	MOHS	n/a
PEI	4	Tile thickness	9 mm
Frost Resistance	Yes	Chemical Resistance	MINGB
Friction Coefficient	n/a	Variation	V1 V2 V3 V4 Moderate
Slip Resistance	n/a		
Water Absorption	≤ 0.5%		

Sizes and Finishes

Rectified	24x24, 24x48			
Non-Rectified	12x24			
Atlantis Ghiaccio		✓	✓	✓
Atlantis Perla		✓	✓	✓
Atlantis Fumo		✓	✓	✓
Atlantis Sabbia		✓	✓	✓
Atlantis Lava		✓	✓	✓

Special instructions

Shade variations between tiles is characteristic. Colour may vary from sample. Technical data is supplied by the manufacturer and is subject to change at anytime. For rectangular tiles, for both floor and wall applications, it is not recommended to be installed using a 50/50 brick pattern. The only brick patterns acceptable are 40/60 or 30/70.

Burnaby: 4330 Halifax Street T: 604-298-6252
 Port Coquitlam: 1110-1579 Kingsway Ave T: 778-948-9854
 Nanaimo: 4337 Boban Drive T: 250-729-9766
 Courtenay: 2-2989 Kilpatrick Ave T: 250-871-3122

