



citytile

Nanaimo:
4337 Boban Drive, Nanaimo, BC 250-729-9766

Courtenay:
#2-2989 Kilpatrick Ave, Courtenay, BC 250-871-3122

STOCKED IN BOTH LOCATIONS 2 CM PORCELAIN PAVERS



BST01 GRAPHITE



BST02 GREY



BST03 SLATE GREY



BST04 IVORY



SDS02-S
ARCTIC WIND




SLT015
DUBAN SLATE




TRV01 BEIGE TRAV



SICILY SAND



SICILY NERO



SICILY BIANCO



SICILY GREY



GP017A BLACK (PROMOTIONAL SALE)

SPECIAL ORDER PAVERS - STOCK AND AVAILABILITY IS SUBJECT TO CHANGE AND SHIPPING RATES WILL APPLY




CEPPO IVORY



CEPPO SILVER




CEPPO GREY



BLENDSTONE
IVORY



BLENDSTONE
SABBIA



BLENDSTONE
TORTORA



BLENDSTONE
ANTRACITE



PROJECT SILVER



PROJECT GRIGIO



BASIC 1 (6009)



COLORADO
LIGHT GREY




ARKETY DK. GREY




ARKETY LT. GREY



ARKETY SILVER




LAKESTONE WHITE




LAKESTONE
DK. GREY



LAKESTONE
LT. GREY



LAKESTONE
ANTRACITE



PROJECT NERO



PROJECT CEMENTO



BASIC 4 (6043)



COLORADO
DARK GREY

Product Code	Height/Thickness	Profile	Height	Height/Profile	Profile
EN-CO-A	20.29mm (0.79"-1.14")		3mm ^Ø spacer tube		30 pcs/cft
			A-base		30 pcs/cft
EN-CO-B	29.40mm (1.14"-1.65")		3mm ^Ø spacer tube		30 pcs/cft
			B-base		30 pcs/cft
EN-CO-C	42.40mm (1.65"-2.38")		3mm ^Ø spacer tube		30 pcs/cft
			C-base		30 pcs/cft
EN-CO-D	60.95mm (2.36"-3.14")		3mm ^Ø spacer tube		30 pcs/cft
			D-base		30 pcs/cft

ALL SIZES 2cm Compliant with standards EN 14411 annex G group B/A Compliant with standards ISO 19600 annex G group B/A

PROPERTIES	TEST METHOD	REQUIREMENTS	RESULTS
LENGTH AND WIDTH	ISO 10545-2	±2.0mm ±0.4%	+0.2mm +0.03% → +0.04%
THICKNESS	ISO 10545-2	±0.5mm ±5%	0mm -0.38% → +0.31%
WATER ABSORPTION	ISO 10545-3	E ≤ 0.3% individual maximum 0.6%	0.00% 0.07% → 0.10%
BREAKING STRENGTH (IN)	ISO 10545-4	5 ± 1300 N	5 ± 999N
ABRASION RESISTANCE	ISO 10545-7	Report cycles/Class	Passed 2100/Class 4
THERMAL SHOCK RESISTANCE	ISO 10545-9	PASS	Fully Resistant
CRAZING RESISTANCE	ISO 10545-11	PASS	Fully Resistant
FROST RESISTANCE	ISO 10545-12	PASS	Fully Resistant
SLIP RESISTANCE	DN 51130	Declared value	22.4° Class R11
STAIN RESISTANCE	ISO 10545-14	Minimum Class 3	Class 5
HOUSEHOLD CHEMICAL RESISTANCE	ISO 10545-13	Minimum Class B	GLAVI
RESISTANCE TO LOW CONCENTRATIONS OF ACIDS & ALKALIS	ISO 10545-13	Declared value	GLAVI
RESISTANCE TO HIGH CONCENTRATIONS OF ACIDS & ALKALIS	ISO 10545-13	Declared value	GHAVI

Assembly Guide
Complete installation guide is available, please inquire.

